






Liesegang Data- and videoprojectors

Liesegang technology Vertriebsgesellschaft mbH
 Nueningstrasse 13 · D-45141 Essen
 Phone: +49 (0)2 01-89 070-0 · Fax: +49 (0)2 01-89 070-18
 info@Liesegang.com · www.Liesegang.com

Technical Specifications*	Liesegang dv 481	Liesegang dv 483	Liesegang dv 486plus	Liesegang dv 488active	NEW! Liesegang dv 900
					
	Entry-projector with 2,200 ANSI lumens. Excellent equipment for the small budget.	Ideal for medium-sized school- and conference rooms. Extensive features like Unplug&Go, Wide-angle lens and Vertical Keystone Correction.	Ideal for large rooms, like assembly halls and conference rooms. Extensive features like Unplug&Go, Wide-angle lens and Vertical Keystone Correction.	Projector with Whiteboard Function. No asset- and assembly costs for a whiteboard. Extensive features. Convincing price.	Installation projector - ideal for use in large seminar and conference rooms. Extensive equipment features for flexible use.
General	dv 481	dv 483	dv 486plus	dv 488active	dv 900
Technology	3x 0.63" p-Si LCD	3x 0.63" p-Si LCD	3x 0.63" p-Si LCD	3x 0.63" p-Si LCD	3x 0.8" p-Si LCD
Resolution	XGA, 1.024 x 768 pixel	XGA, 1.024 x 768 pixel	XGA, 1.024 x 768 pixel	XGA, 1.024 x 768 pixel	XGA, 1.024 x 768 pixel
Brightness Standard mode	2.200 ANSI lumens	2.600 ANSI lumens	3.200 ANSI lumens	2.800 ANSI lumens	4.500 ANSI lumens
Brightness Whisper mode	k.A.	2.080 ANSI lumens	2.600 ANSI lumens	2.240 ANSI lumens	3.800 ANSI lumens
Contrast ratio	500:1	500:1	500:1	500:1	500:1
Weight	2.9 kgs	2.9 kgs	2.9 kgs	2.9 kgs	<7.5 kgs
Dimensions W x H x D	310 x 96 x 270 mm	310 x 96 x 270 mm	310 x 96 x 270 mm	310 x 96 x 270 mm	480 x 145 x 360 mm
Noise Level	30 dB	30 dB in whisper mode	30 dB in whisper mode	30 dB in whisper mode	30 dB Whisper mode
Lamp, Lifetime*	180 W NSH, up to 3.000 hours	180 W NSH, up to 3.000 hours in whisper mode	205 W NSH, up to 3.000 hours in whisper mode	180 W NSH, bis zu 3.000 hours in whisper mode	275 W NSH, up to 3.000 hours in whisper mode
Keystone correction	+/-30° vertical	+/-30° vertical	+/-30° vertical	+/-30° vertical	+/-30° vertical
Scanning frequency Hsync / Vsync	15-69 kHz / 43-85 Hz	15-69 kHz / 43-85 Hz	15-69 kHz / 43-85 Hz	15-69 kHz / 43-85 Hz	15-107 kHz / 50-120 Hz
Speaker	2 x 1 W	2 x 1 W	2 x 1 W	2 x 1 W	1x 8 W
Power Consumption	250 W	250 W	250 W	250 W	350 W
Lens	F=1.66-1.88, f=18.6-22.3 mm, 1.2x manual zoom	F=1.66-1.88, f=18.6-22.3 mm, 1.2x manual zoom	F=1.66-1.88, f=18.6-22.3 mm, 1.2x manual zoom	F=1.66-1.88, f=18.6-22.3 mm, 1.2x manual zoom	F=1.7-1.9, f=23.3-28.2 mm, 1.2-fach Zoom manual
Projection distance/diagonal (min.-max.)	1,2 - 9,1 m / 0,77 - 7,70 m	1,2 - 9,1 m / 0,77 - 7,70 m	1,2 - 9,1 m / 0,77 - 7,70 m	1,2 - 9,1 m / 0,77 - 7,70 m	1,2 - 9,1 m / 1,0 - 7,62 m
Connectors	dv 481	dv 483	dv 486plus	dv 488active	dv 900
Computer in	2x RGB analog	2x RGB analog	1x RGB analog, 1x DVI input	2x RGB analog	1x DVI, 1x RGB analog
Control (Handling and mouse)	1x RS-232, 1x USB (mouse)	1x RS-232, 1x USB (mouse)	1x RS-232, 1x USB (mouse)	1x RS-232, 1x USB (Maus)	1x RS-232, 1x USB (Mouse)
Video in	1x Video, 1x S-Video, 1x Component (RGB-analog)	1x Video, 1x S-Video, 1x Component (RGB-analog)	1x Video, 1x S-Video, 1x Component (RGB-analog)	1x Video, 1x S-Video, 1x Component (RGB-analog)	Composite Video: 1x Video, 1x S-Video, 2x Audio Component Video: 3x Component, 2x Audio
Audio in	1x Audio Stereo	1x Audio Stereo	1x Audio Stereo	1x Audio Stereo	2x Audio Stereo
Computer out	1x RGB analog	1x RGB analog	1x RGB analog	1x RGB analog	1x RGB analog
Audio out	1x Audio Stereo	1x Audio Stereo	1x Audio Stereo	1x Audio Stereo	1x Audio Stereo
Special Features	dv 481	dv 483	dv 486plus	dv 488active	dv 900
	· Wide-angle lens	· Wide-angle lens	· Wide-angle lens	· Projector with Whiteboard Function	· Wide-angle lens
	· Colour temperature individual adjustable	· Unplug & Go function	· Unplug & Go function	· Extremely wide-angled lens	· Vertical Keystone Correction +/-30°
	· Automatic Keystone correction switchable	· Colour temperature individual adjustable	· Colour temperature individual adjustable	· Unplug & Go function	· Quick Start Function
	· 6 times Digital zoom	· Automatic Keystone correction switchable	· Automatic Keystone correction switchable	· Automatic Keystone correction switchable	· High-Altitude-Mode
	· Monitor output	· 6 times Digital zoom	· 6 times Digital zoom	· 6 times Digital zoom	· 1 W power consumption in standby
		· Monitor output	· Monitor output	· Monitor output	· HEPA Filter