

TOSHIBA
Leading Innovation >>>



EW25 Extreme short throw projector in widescreen

Want to make a widescreen impression in a narrow place? Here's the answer! The EW25 only needs to be half a metre from the wall in order to project a breath-taking widescreen image. Using "Windows Vista® Network" functionality, it can be easily connected to the network over WLAN. Or plug your USB stick directly into the USB connector and away you go!



WIDESCREEN = BIG IMPRESSION

The EW25 business projector features a revolutionary innovation called ESP, which stands for 'Extreme Short-throw Projector' so now you can show people the full picture even in the most intimate surroundings.

The EW25 is ideal for corporate, government and educational organisations as it's easily transportable and extremely versatile thanks to a full menu of inputs, outputs and extras.

It's brilliant in other ways too with 2,600 ANSI-lumens of brightness and WXGA 1,280x800 display.

The new Brilliant Color™ technology by Texas Instruments and the powerful NCE 4™ chip provide extraordinary lifelike colour and all other technical characteristics are also in a class of their own.

In addition, the EW25 features remote control with laserpointer, password protection and panel lock for ultimate security, digital zoom, and programmable user logo.

KEY BENEFITS

3 year warranty with
90 day replacement warranty
and 90 day lamp warranty

**Windows Vista® Network
(WLAN and LAN)**

BrilliantColor™ and NCE 4™

Only 4.2 kilograms

Wireless connectivity

WXGA 1,280 x 800 resolution

Specifications

Device	0.65" DMD™ Chip
Resolution	WXGA 1280 x 800 pixels
Brightness	Standard - 2600lm / ECO - 2000lm
Contrast	2000 : 1
Lamp	Standard - 275W / Low - 220W
Lamp Life	Standard - 2000H / Low - 3000H
Replacement Lamp	TLPLW15 lamp
Input signals	- NTSC/PAL/SECAM, 480i, 480p, 576i, 576p, 720p, 1,080i - VGA / SVGA / XGA (True) / WXGA / SXGA / UXGA (Compressed)

Video Processor	DDP2230
Lens	F = 2.6 - 8.37, manual focus
Colour Temperature	6400K +1500K, -1000K
Picture size (diagonal)	1.02 - 3.05m
Projection distance	- 0.5 - 1.5m - Optical offset 100%
Inputs	- RGB (2 x D-sub 15) - S-Video (1 x S Terminal) - Composite Video (1 x RCA) - Audio (Stereo Mini Jack) - Video / S-Video Audio (2 x RCA L/R) - Component (Y/PB/PR) via shared RGB terminal

Outputs	- RGB (D-sub 15) - Audio (Stereo Mini Jack)
Other Terminals	- RS-232C (D-SUB 9pin) - RJ-45 - USB (Type A)
Integrated loudspeaker	1 W (mono)
Dimensions (W x H x D)	- W/o Protruding Parts 337 x 118 x 265 mm - W/ Protruding Parts 338 x 132 x 267
Volume	10.5L
Weight	4.2 kilogram

Extras	- Auto Keystone Correction - digital zoom - BrilliantColour™ - Windows Vista™ Network (WLAN & LAN) - USB - password - panellock - user logo - DDC compatible
Accessories	- remote control with laserpointer - owners manual (CD ROM) - quick reference - RGB and power-cable - softcase
Options	- ceiling mount - spare lamp - camera c001